

ACCLAIM

RIGID CORE ABA SPC LUXURY VINYL with Premium Attached Pad

ERDINGER OAK

Superior Dimensional Stability

The Rigid Core ABA structure provides an enhanced dimensional stability in areas prone to issues related to expansion and contraction.

Specifications


Dimensions (nominal)	4.5 mm thick overall x 7.25" W x 48" L
Construction	3.5 mm core plus 1 mm attached IXPE pad
Finish Coat	Polyurethane + Anti-Microbial & Anti-Scratch Coating
Wear Layer	12 mil
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Installation	Angle/Angle, Float
Warranty	25 Yr Residential, 5 Yr Light Commercial, 5 Yr Multi-Family
Packaging	28.84 sf/ctn, 55 ctn/plt, 1586.2 sf/plt

DID YOU KNOW?



LOCALLY STOCKED IN KENT, WA

Acclaim is stocked heavily in Kent, WA. What you need, when you need it.



ABA CONSTRUCTION

The ABA layered construction of Acclaim provides superior dimensional stability in a rigid core product.



PEACE OF MIND ANTI-MICROBIAL COATING

Our anti-microbial coating prevents the growth and spreading of mold and bacteria on top of the floor.



COMFORT UNDER FOOT

Premium attached IXPE pad reduces sound transfer, provides for an easy and quick installation and adds comfort underfoot.

FOR MORE INFORMATION

marketingta@tasupply.com
tasflooring.com

6807 South 216th St
Kent, WA 98032



A Division of

T&A supply company, Inc.