

SPC 5.0 MM, 20 MIL



Ozet | NFRCU0202



Cruiser | NFRCU0203



Crescent | NFRCU0204



Whiskey | NFRCU0205



Pyramid | NFRCU0207



Cairns | NFRCU0208

SPECIFICATIONS

Construction	SPC Rigid Core, Stone Polymer Composite
Dimensions	9" Wide x 60" Long, 230 mm x 1524mm
Overall Thickness	5.0 mm (includes 1 mm pad)
Wear Layer	20 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	4-Sided Micro Bevel
Installation	Angle / Angle
Warranty	30 Yr Residential, 10 Yr Light Commercial, 10 Yr Multi-Family,
Packaging	26.37 sf/carton - 48 carton/pallet - 1265.76 sf/pallet

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Recommended Room Temp: 60°F-85°F after install
- Expansion Space: 1/4" gap
- Transition required for rooms larger than 50'W x 50'L
- Subfloors dry and flat (3/16" in 10')

Read Complete Instructions Before Installing



**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & Q&A**

tasflooring.com

