

PLANKS



Cyprus
TPWP0401



Timberline
TPWP0402



Ironwood
TPWP0403



Northern Pine
TPWP0404



Canyon Hills
TPWP0405



Flask
TPWP0406



Ocean View
TPWP0410



Natural Acacia
TPWP0411



American Walnut
TPWP0412



Scandinavian Oak
TPWP0413



Nordic Oak
TPWP0414



Ventura
TPWP0425



Torrance
TPWP0426



Sojourn
TPWP0427



McKenna
TPWP0428



Distinctive
TPWP0429

TILES



Pello Rock
Natural
TPWPDLO417



Pello Rock
Sandstone
TPWPDLO418




Italian Stone
Grigio
TPWPDLO419




Italian Stone
Crema
TPWPDLO420



Concrete Stain
Naturelle
TPWPDLO421



Concrete Stain
Marrone
TPWPDLO422



Carrara Marble
TPWPDLO423



Limestone Vein Cut
TPWPDLO424

Sparta Premium Luxury Vinyl checks ALL the boxes!



SCRATCH & SCUFF RESISTANT

20mil wear layer provides premium surface protection.



THICKER IS BETTER

More support, warmth, and comfort under foot.



BLOCK-AID CORE

Protects your floor from changes due to temperature and adds to the floors durability.



ANTI-MICROBIAL

Protects against the growth of bacteria, keeping your floors cleaner and your family safer.



SPLASH SHIELD WITH ARMOR GUARD

Surface water protection for your peace of mind.

PRODUCT SPECIFICATIONS

Dimensions: (nominal)

Plank - 7" wide x 48" long
Tile - 11.8" wide x 23.6" long
8 mm overall thickness

Construction:

Waterproof Engineered Vinyl Clic Plank & Tile, 6.5 mm Block-Aid core plus 1.5 mm Premium Pad

Wear Layer: 20 mil

Finish Coat: Polyurethane, Anti-Microbial, and Anti-Scratch Coatings

Profile:

Plank - Micro Bevel
Tile - Painted Bevel

Installation:

Plank - Angle/Angle
Tile - Angle/Drop/Tap

Warranty: Lifetime Residential, 10 Year Light Commercial, 10 Year Multi-Family

Acoustic Rating: IIC 57

Installation References:

Read Complete Instructions Before Installing

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate to normal room conditions
- Relative Humidity(RH): 35%-55%
- Recommended Room Temp: 60°-85° after install
- Expansion Space:1/4" gap
- Transitions not required in rooms up to 50' w in any direction or 2,500sf

